



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
Hazardous Substances (Safety Data Sheets) Notice 2017 EPA Consolidation 30
September 2022

BOSTIK NO 3 SOLVENT
Revision Number 1

Revision date 08-Apr-2025
Supersedes date 27-Mar-2022

Section 1: Identification

Product identifier

Product Name BOSTIK NO 3 SOLVENT

Other means of identification

Recommended use of the chemical and restrictions on use

Recommended use Cleaning agent Solvent mixture

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier

Bostik New Zealand Limited
19 Eastern Hutt Road Wingate,
Lower Hutt, New Zealand
Tel: 04-567 5119
Fax: 04-567 5412

Manufacturer

Bostik New Zealand Limited
19 Eastern Hutt Road Wingate,
Lower Hutt, New Zealand
Tel: 04-567 5119
Fax: 04-567 5412

E-mail address SDS.AP@Bostik.com

Emergency telephone number

Emergency Telephone 24 Hr: 0800 243 622
International +64 4 917 9888
Poison Centre : 0800 764 766

Section 2: Hazard identification

GHS Classification

Flammable liquids	Category 2
Aspiration hazard	Category 1
Skin corrosion/irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Hazardous to the aquatic environment - acute	Category 1
Hazardous to the aquatic environment - chronic	Category 1

Label elements



Signal word
Danger

Hazard statements

SAFETY DATA SHEET

BOSTIK NO 3 SOLVENT
Revision Number 1

Revision date 08-Apr-2025
Supersedes date 27-Mar-2022

H225 - Highly flammable liquid and vapor
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H336 - May cause drowsiness or dizziness
H410 - Very toxic to aquatic life with long lasting effects

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling
Avoid breathing dust, fume, gas, mist, vapors and spray
Use only outdoors or in a well-ventilated area
Avoid release to the environment
Ground and bond container and receiving equipment
Use non-sparking tools
Take action to prevent static discharges
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
Keep container tightly closed
Wear protective gloves, protective clothing, eye protection and face protection
Keep cool
Use explosion-proof electrical/ ventilating/ lighting/ equipment

Precautionary Statements - Response

Skin

If skin irritation occurs: Get medical advice/attention
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
Wash contaminated clothing before reuse

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing
Call a POISON CENTER or doctor if you feel unwell

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor
Do NOT induce vomiting

Fire

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

Spill

Collect spillage

Precautionary Statements - Storage

Store locked up
Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents and container in accordance with local, regional, national, and international regulations as applicable

Other hazards which do not result in classification

May be harmful if inhaled. In use, may form flammable/explosive vapor-air mixture.

Section 3: Composition/information on ingredients

Chemical name	CAS No.	Weight-%
Heptane	142-82-5	40 - <80
Cyclohexane	110-82-7	20- <40
Methylcyclopentane	96-37-7	5 - <10
Octane	111-65-9	5 - <10

Section 4: First-aid measures

Description of first aid measures

SAFETY DATA SHEET

BOSTIK NO 3 SOLVENT
Revision Number 1

Revision date 08-Apr-2025
Supersedes date 27-Mar-2022

General advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Inhalation	Remove to fresh air. Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get medical attention if irritation develops and persists.
Ingestion	Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Get immediate medical attention.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms	Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.
Effects of Exposure	No information available.

Indication of any immediate medical attention and special treatment needed

Note to physicians	Because of the danger of aspiration, emesis or gastric lavage should not be employed unless the risk is justified by the presence of additional toxic substances.
--------------------	---

Section 5: Fire-fighting measures

Suitable Extinguishing Media

Suitable Extinguishing Media	Dry chemical. Carbon dioxide (CO ₂). Water spray. Alcohol resistant foam.
Large Fire	CAUTION: Use of water spray when fighting fire may be inefficient.
Unsuitable extinguishing media	Do not scatter spilled material with high pressure water streams.

Specific hazards arising from the chemical

Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Hazardous combustion products	Carbon oxides.

Special protective actions for fire-fighters

Special protective equipment and precautions for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear.
--	---

SAFETY DATA SHEET

BOSTIK NO 3 SOLVENT
Revision Number 1

Revision date 08-Apr-2025
Supersedes date 27-Mar-2022

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions	Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.
Other information	Ventilate the area. Refer to protective measures listed in Sections 7 and 8.
For emergency responders	Use personal protection recommended in Section 8.

Environmental precautions

Environmental precautions	Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.
----------------------------------	--

Methods and material for containment and cleaning up

Methods for containment	Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.
Methods for cleaning up	Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

Precautions to prevent secondary hazards

Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.
--	--

Section 7: Handling and storage

Precautions for safe handling

Advice on safe handling	Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. In case of insufficient ventilation, wear suitable respiratory equipment.
General hygiene considerations	Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection.

Conditions for safe storage, including any incompatibilities

Storage Conditions	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible
---------------------------	--

SAFETY DATA SHEET

BOSTIK NO 3 SOLVENT
Revision Number 1

Revision date 08-Apr-2025
Supersedes date 27-Mar-2022

materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children. Store away from other materials. Protect from moisture.

Recommended storage temperature

Keep at temperatures between 41 and 77 °F / 5 and 25 °C.

Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents.

Section 8: Exposure controls/personal protection

Working area parameters, subject to mandatory control (MAC or TSEL)

Exposure Limits

Chemical name	New Zealand	ACGIH TLV	United Kingdom	Australia
Heptane 142-82-5	TWA: 400 ppm; TWA: 1640 mg/m ³ ; STEL: 500 ppm; STEL: 2050 mg/m ³ ;	TWA: 400 ppm STEL: 500 ppm	TWA: 500 ppm; TWA: 2085 mg/m ³ ; STEL: 1500 ppm; STEL: 6255 mg/m ³ ;	TWA: 400 ppm; TWA: 1640 mg/m ³ ; STEL: 500 ppm; STEL: 2050 mg/m ³ ;
Cyclohexane 110-82-7	TWA: 100 ppm; TWA: 350 mg/m ³ ; STEL: 300 ppm; STEL: 1050 mg/m ³ ;	TWA: 100 ppm	TWA: 100 ppm; TWA: 350 mg/m ³ ; STEL: 300 ppm; STEL: 1050 mg/m ³ ;	TWA: 100 ppm; TWA: 350 mg/m ³ ; STEL: 300 ppm; STEL: 1050 mg/m ³ ;
Octane 111-65-9	TWA: 300 ppm; TWA: 1400 mg/m ³ ; STEL: 375 ppm; STEL: 1750 mg/m ³ ;	TWA: 300 ppm	-	TWA: 300 ppm; TWA: 1400 mg/m ³ ; STEL: 375 ppm; STEL: 1750 mg/m ³ ;

Biological occupational exposure limits

Chemical name	New Zealand	ACGIH
Cyclohexane 110-82-7	-	50 mg/g creatinine - urine (1,2-Cyclohexanediol) - end of shift at end of workweek

Appropriate engineering controls

Engineering controls

Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eyeface protection

Tight sealing safety goggles.

Hand protection

Wear suitable gloves. Impervious gloves.

Skin and body protection

Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Antistatic boots.

Respiratory protection

No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Environmental exposure controls

No information available.

SAFETY DATA SHEET

BOSTIK NO 3 SOLVENT
Revision Number 1

Revision date 08-Apr-2025
Supersedes date 27-Mar-2022

Section 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state	Liquid
Appearance	Solid Paste Liquid
Color	Clear, colorless
Odor	Solvent.
Odor threshold	No information available

Property	Values	Remarks • Method
pH	No data available	Not applicable Insoluble in water
Melting point / freezing point	No data available	None known
Initial boiling point and boiling range	75 °C	
Flash point	-15 °C	
Evaporation rate	No data available	None known
Flammability	No data available	Flammable liquid
Flammability Limit in Air		None known
Upper flammability or explosive limits	7.5	
Lower flammability or explosive limits	1.0	
Vapor pressure	No data available	None known
Relative vapor density	No data available	None known
Relative density	No data available	None known
Water solubility	Insoluble in water	
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature		None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	
Explosive properties	No information available.	
Oxidizing properties	No information available.	

Other information

Softening point	No information available
Molecular weight	No information available
VOC content	No information available
Density	0.72 g/cm ³
Bulk density	No information available
Particle characteristics	

Section 10: Stability and reactivity

Reactivity

Reactivity	No information available.
------------	---------------------------

Chemical stability

Stability	Stable under normal conditions.
-----------	---------------------------------

Explosion data

Sensitivity to mechanical impact	None.
----------------------------------	-------

Sensitivity to static discharge	Yes.
---------------------------------	------

Possibility of hazardous reactions

SAFETY DATA SHEET

BOSTIK NO 3 SOLVENT
Revision Number 1

Revision date 08-Apr-2025
Supersedes date 27-Mar-2022

Possibility of hazardous reactions None under normal processing.

Conditions to avoid

Conditions to avoid Heat, flames and sparks. Protect from moisture.

Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidizing agents.

Hazardous decomposition products

Hazardous decomposition products None known based on information supplied.

Section 11: Toxicological information

Acute toxicity

Information on likely routes of exposure

Product Information

Inhalation	Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract. May cause drowsiness or dizziness. May be harmful if inhaled.
Eye contact	Specific test data for the substance or mixture is not available. May cause irritation.
Skin contact	Repeated exposure may cause skin dryness or cracking. Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components).
Ingestion	Specific test data for the substance or mixture is not available. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Symptoms	Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Redness. May cause redness and tearing of the eyes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Acute toxicity

Numerical measures of toxicity

The following ATE values have been calculated for the mixture

ATEmix (oral)	>5000 mg/kg
ATEmix (dermal)	>5000 mg/kg
ATEmix (inhalation-gas)	>20000 ppm
ATEmix (inhalation-vapor)	>20 mg/l
ATEmix (inhalation-dust/mist)	48.02 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Heptane	LD50 > 5000 mg/Kg (rattus)	= 3000 mg/kg (Oryctolagus cuniculus)	=103 g/m ³ (Rattus) 4 h
Cyclohexane	=12705 mg/kg (Rattus)	> 2000 mg/kg (Oryctolagus cuniculus)	>9500 ppm (Rattus) 4 h

SAFETY DATA SHEET

BOSTIK NO 3 SOLVENT
Revision Number 1

Revision date 08-Apr-2025
Supersedes date 27-Mar-2022

Octane	>5000 mg/Kg (Rattus)	-	=118 g/m ³ (Rattus) 4 h = 25260 ppm (Rattus) 4 h > 23.36 mg/L (Rattus) 4 h
--------	----------------------	---	---

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes skin irritation.

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitization Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Heptane (142-82-5)

Method	Species	Results
OECD Test No. 473: In vitro Mammalian Chromosome Aberration Test	Rat, in vitro	Not mutagenic
OECD Test No. 471: Bacterial Reverse Mutation Test		Not mutagenic in AMES Test

Carcinogenicity No information available.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure May cause drowsiness or dizziness.

Narcotic effects Narcotic effects.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard May be fatal if swallowed and enters airways.

Section 12: Ecological information

Ecotoxicity

Ecotoxicity Very toxic to aquatic life with long lasting effects.

Aquatic ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Crustacea
Heptane	-	LC50: =375.0mg/L (96h, Cichlid)	EC50: >10mg/L (24h, Daphnia magna)
Cyclohexane	EC50 72 h > 9.3 mg/L (Pseudokirchnerella subcapitata)	LC50: 23.03 - 42.07mg/L (96h, Pimephales promelas) LC50: 48.87 - 68.76mg/L (96h, Poecilia reticulata) LC50: 3.96 - 5.18mg/L (96h, Pimephales promelas) LC50: 24.99 - 44.69mg/L (96h, Lepomis macrochirus)	EC50: >0.9 mg/L (24h, Daphnia magna)
Octane	-	-	EC50: =0.38mg/L (48h, Daphnia magna)

SAFETY DATA SHEET

BOSTIK NO 3 SOLVENT
Revision Number 1

Revision date 08-Apr-2025
Supersedes date 27-Mar-2022

Terrestrial ecotoxicity There is no data for this product.

Persistence and degradability No information available.

Bioaccumulative potential
Bioaccumulation
Component Information

Chemical name	Partition coefficient
Heptane	4.66
Cyclohexane	3.44
Octane	5.18

Mobility in soil

Mobility No information available.

Other adverse effects

No information available.

Disposal methods

Waste from residues/unused products

Dispose of product in packaging in a way that is consistent with the EPA Consolidation 30 April 2021 of the Hazardous Substances (Disposal) Notice 2017 and the Act. Treat the substance using a method that changes the characteristics or composition of the substance so that the substance is no longer a hazardous substance; or export the substance from New Zealand as waste. Flammable substances - may not be disposed of into or onto a landfill or sewage facility.

They may only be burnt in certain situations.

Flammable gases, liquids and solids may only be discharged into the environment or landfill as waste if the substance will not at any time come into contact with any explosives, oxidising gases, liquids or solids or organic peroxides; and there will be no ignition source in the vicinity of the disposal site at any time and if the substance were to ignite, no person, or place where a person may legally be, would be exposed to an unsafe level of heat radiation. Substances which are hazardous to human health or corrosive to metals – may be discharged into the environment if a tolerable exposure limit has been set for the substance (or a component of that substance); and the discharge does not, after reasonable mixing, result in the concentration of the substance in an environmental medium exceeding the tolerable exposure limit. If there is no tolerable exposure limit for the substance, then it may only be discharged into the environment if the substance is very rapidly converted to substances that are not hazardous substances. Environmentally hazardous substances – if the substance, or if it contains a component that is hazardous to the aquatic environment or bioaccumulative and not rapidly degradable, then any component that is bioaccumulative and not rapidly degradable must be removed. The product may only be discharged into the environment if an environmental exposure limit has been set for the substance (or a component of the substance); and the discharge does not, after reasonable mixing, result in the concentration of the substance in an environmental medium exceeding the environmental exposure limit.

Contaminated packaging

For packages that have been in direct contact with hazardous substances, the person must ensure that the package is rendered incapable of containing any substance. It must be disposed of in a manner that is consistent with the requirements for disposal of the substance that it contained, taking into account the material the package is manufactured from. Packages may only be reused or recycled if:

- the substance has a physical hazard other than corrosive to metal, and has been

SAFETY DATA SHEET

BOSTIK NO 3 SOLVENT
Revision Number 1

Revision date 08-Apr-2025
Supersedes date 27-Mar-2022

treated to remove any residual contents of the hazardous substance;
- or for substances that have a health or environmental hazard, or corrosive to metal, the contents of the residue in the package are below the threshold for the substance to be classified as hazardous in the Hazardous Substances (Hazard Classification) Notice 2020.

Section 14: Transport information

IATA

UN number or ID number	UN1268
UN proper shipping name	Petroleum distillates, n.o.s.
Transport hazard class(es)	3
Packing group	II
Special Provisions	A3
Description	UN1268, Petroleum distillates, n.o.s., 3, II

IMDG

UN number or ID number	UN1268
UN proper shipping name	Petroleum distillates, n.o.s.
Transport hazard class(es)	3
Packing group	II
EmS-No.	F-E, S-E
Marine pollutant	P
Description	UN1268, Petroleum distillates, n.o.s. (Heptane), 3, II, (-15°C c.c.), Marine pollutant

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No information available

ADR

UN number or ID number	UN1268
UN proper shipping name	Petroleum distillates, n.o.s.
Transport hazard class(es)	3
Labels	3
Packing group	II
Description	UN1268, Petroleum distillates, n.o.s., 3, II, (D/E), Environmentally Hazardous
Environmental hazards	Yes
Limited quantity (LQ)	1 L
Special Provisions	640C, 664
Classification code	F1
Tunnel restriction code	(D/E)

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

EPA New Zealand HSNO approval code or group standard HSR002662 - Surface Coatings and Colourants (Flammable)

National regulations There are no applicable tolerable exposure limits or environmental exposure limits according to the EPA Controls for Hazardous Substances

Certified handlers, tracking and controlled substance license requirements Certified handlers are required for some substances. This includes substances requiring a controlled substance license, and most explosives, vertebrates toxic agents, and certain fumigants. Acutely toxic substances which are a Category 1 or 2, such as pesticides also require Certified handlers. Please check the Health and Safety at Work Act 2015 for further information

SAFETY DATA SHEET

BOSTIK NO 3 SOLVENT
Revision Number 1

Revision date 08-Apr-2025
Supersedes date 27-Mar-2022

Tracking is required for some highly hazardous substances. These substances need to be under the control of an appropriately trained person or appropriately secured. Please check the Health and Safety at Work Act 2015 for further information
Controlled substance licenses are required to possess certain explosives, vertebrate toxic agents and fumigants. See Part 7 of the Health and Safety at Work Regulation 2017 for more information

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

Europe

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorization:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Section 16: Other information

Prepared By Product Stewardship and Regulatory Affairs
Revision date 08-Apr-2025

Revision Note

***Indicates updated data since last publication.

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend

SVHC: Substances of Very High Concern for Authorization:
PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances
vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances
STOT: Specific Target Organ Toxicity
ATE: Acute Toxicity Estimate
LC50: 50% Lethal Concentration
LD50: 50% Lethal Dose

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	Sk*	Skin designation
**	Hazard Designation	+	Sensitizers
C	Carcinogen		

Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR)
U.S. Environmental Protection Agency ChemView Database
European Food Safety Authority (EFSA)
Environmental Protection Agency
Acute Exposure Guideline Level(s) (AEGl(s))
U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
U.S. Environmental Protection Agency High Production Volume Chemicals
Food Research Journal
Hazardous Substance Database
International Uniform Chemical Information Database (IUCLID)
National Institute of Technology and Evaluation (NITE)
Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)
NIOSH (National Institute for Occupational Safety and Health)

SAFETY DATA SHEET

BOSTIK NO 3 SOLVENT
Revision Number 1

Revision date 08-Apr-2025
Supersedes date 27-Mar-2022

National Library of Medicine's ChemID Plus (NLM CIP)
National Library of Medicine's PubMed database (NLM PUBMED)
U.S. National Toxicology Program (NTP)
New Zealand's Chemical Classification and Information Database (CCID)
Organization for Economic Co-operation and Development Environment, Health, and Safety Publications
Organization for Economic Co-operation and Development High Production Volume Chemicals Program
Organization for Economic Co-operation and Development Screening Information Data Set
World Health Organization

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet